

RG178 B/U

RG-Cables acc. to MIL-C-17F and MIL-C-17G



Application

whole field of commercial electronics and radio frequency engineering

Standards

MIL-C-17F, MIL-C-17G

Flame resistance

IEC 60332-1

Construction

Inner conductor	Stranded copperclad steel wires, silver coated 7 x 0.102, diameter 0.31± 0,01
Insulation	PTFE, diameter 0.84 ± 0.05 mm
Outer conductor	
Copper braid	Silver coated, 96% optical coverage
Sheath	FEP, diameter 1.80 ± 0.10 mm

Mechanical properties

Minimum bending radius	without load	5x outer diameter
	with load	10x outer diameter
Operating temperature		- 70°C up to + 200°C

Electrical properties

at 20°C

DC resistance	Inner conductor	≤ 800 Ω/km
Characteristic impedance		50 ± 2 Ω
Mutual capacitance		96 pF/m
Velocity ratio		70 %
Operating voltage RF		1.0 kV Peak
Test voltage		
Inner/Outer conductor		2 kV _{rms}

RG178 B/U

Electrical data

at 20°C

Frequency (MHZ)	Attenuation (dB/100m)	Max. power rating (Watts) (ambient temperature 40°C)
	nominal	maximum
100	46	240
200	62	180
400	92	120
1000	151	75

All further requirements acc. to MIL-C 17F respectively MIL-C17G

Technical data

Product code	Designation	Type	Brand name	Outer diameter	Weight	Gross weight	Copper content	Tensile force	Standard delivery length	Drum size
				mm	kg/km	kg/km		N	m	*PWD
1002903	5YC6Y	0.31 Ls/0.824 Staku	M17/93- RG178	1.80	9.0	11	4.7	23	1000	300/150/160

*PWD (Plywood drum)

[PRODUCT CODE TABLE]

© PRYSMIAN GROUP 2008, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.