

# RG214

## RG-Cables acc. to MIL-C-17F and MIL-C-17G



### Application

see product overview

### Standards

acc. to MIL-C-17F and MIL-C-17G

### Flame resistance

acc. to IEC 60332-1

### Construction

Inner conductor	stranded copper wires, silver plated 7 x 0.75, diameter 2.25 ± 0.1 mm
Insulation	PE, diameter 7.25 ± 0.15 mm
1 <sup>st</sup> braid	silver plated, 94% optical coverage
2 <sup>nd</sup> braid	silver plated, 97% optical coverage
Sheath	PVC, diameter 10.80 ± 0.18 mm

### Mechanical properties

Minimum bending radius	without load	5 x outer diameter
	with load	10 x outer diameter
Temperature	during operation	-40° C to + 85° C
	during installation	-15° C to + 55° C

# RG214

## Electrical properties

at 20°C

DC resistance	Inner conductor	5.7 Ω/km
	1 <sup>st</sup> braid	9.6 Ω/km
	2 <sup>nd</sup> braid	8.2 Ω/km
Mutual capacitance		100 pF/m
Characteristic impedance		50 Ω ± 2 Ω
Velocity ratio		66 %
Maximum operating frequency		11 GHz
Operating voltage		3.7 kV <sub>rms</sub>
Test voltage	Inner/Outer conductor	10.0 kV <sub>rms</sub>

## Electrical data

at 20°C

Frequency (MHz)	Attenuation (dB/100m)	Max. power rating (Watts) (ambient temperature 25°C and max. inner conductor temperature 70°C)	Return loss (dB) several peaks are allowed	
			Frequency (MHz)	
50	4.8	1500	100	≥ 23
100	6.9	920	1000	≥ 20
400	15.2	330	3000	≥ 19
1000	26.7	160	5000	≥ 18
3000	54.8	75		
5200	79.8	61		
5800	86.6	56		

All other requirements acc. to MIL-C-17F respectively MIL-C-17G

## Technical data

Product code	Designation	Type	Brand name	Outer diameter	Weight	Standard delivery length	Drum size	Gross weight	Copper content	Tensile force
				mm	kg/km	m	*PWD/rin g	kg		N
1002737	2YCCY	2.25Ls/ 7.25Ds	M17/75- RG214	10.8	200	1000/100	760/360/ 420	212/2 0	132.9	730

\*PWD (Plywood drum)

[PRODUCT CODE TABLE]

**RG214**

---

© PRYSMIAN GROUP 2009, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.