

## RG6

### RG-Cables acc. to MIL-C-17F and MIL-C-17G



## Application

see product overview

## Standards

acc. to MIL-C-17F and MIL-C-17G

## Flame resistance

acc. to IEC 60332-1

## Construction

Inner conductor	copperclad steel wire, diameter $0.73 \pm 0.01$ mm
Insulation	PE, diameter $4.7 \pm 0.05$ mm
1. braid	silver plated , 96% optical coverage
2. braid	bare, 96% optical coverage, diameter 6.2 mm
Sheath	PVC, diameter $8.40 \pm 0.15$ mm

## Mechanical properties

Minimum bending radius	without load	5 x outer diameter
	with load	10 x outer diameter
Temperature	during operation	-40° C to + 85° C
	during installation	-15° C to + 55° C

## Electrical properties

at 20°C

DC resistance	Inner conductor	105 $\Omega$ /km
	1st braid	6.5 $\Omega$ /km
	2nd braid	7.5 $\Omega$ /km
Mutual capacitance		67 nF/m
Characteristic impedance		75 $\Omega \pm 3 \Omega$
Velocity ratio		66 %
Operating voltage		$\leq 2.4$ kV <sub>rms</sub>
Test voltage	Inner-/outer conductor	7.0 kV <sub>rms</sub>

# RG6

## Electrical data

at 20°C

Frequency (MHz)	Attenuation (dB/100m)	Max. power rating (Watts) (ambient temperature 25°C and max. inner conductor temperature 70°C)
10	3.0	1600
100	9.8	500
200	14	340
400	20	220
1000	32	150
2000	47	70
3000	60	50

All other requirements acc. to MIL-C-17F respectively MIL-C-17G

## Technical data

Product code	Designation	Type	Brand name	Outer diameter	Weight	Standard delivery length	Drum size	Gross weight	Copper content	Tensile force
				mm	kg/km	m	*PWD	kg		N
1002714	2YCCY	0.73/4.7 Ds Staku	M17/2-RG6	8.4	115	1000	760/360 / 420	128	70.1	385

\*PWD (Plywood drum)

[PRODUCT CODE TABLE]

© PRYSMIAN GROUP 2008, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.